



ORYZA OIL & FAT CHEMICAL CO.,LTD.

1 Aza Numata Kitagata Kitagata-cho Ichinomiya-city, Aichi-prefecture 493-8001 JAPAN

TEL:+81-586-86-5141 FAX:+81-586-86-6191

URL: <https://www.oryza.co.jp/> E-mail: info@oryza.co.jp

PRODUCT STANDARD

PRODUCT NAME : **ORYZA CERAMIDETM-P10CD** (FOOD)

This product is extracted with hexane and ethanol from rice bran and rice germ of *Oryza sativa* Linne (*Gramineae*). It contains a minimum of 10.0 % Ceramide (Glycosphingolipids).

<u>Appearance</u>	Slightly yellow powder with slightly unique aroma								
<u>Ceramide (Glycosphingolipids)</u>	Min. 10.0 % (Densitometry Method) (HPLC Light Scattering Method)								
<u>Loss on Drying</u>	Max. 10.0 % (Analysis for Hygienic Chemists, 1g, 105 °C, 2 hr)								
<u>Purity Test</u>									
<u>(1) Heavy Metals (as Pb)</u>	Max. 10 ppm (Sodium Sulfide Colorimetric Method)								
<u>(2) Arsenic (as As₂O₃)</u>	Max. 1 ppm (Standard Methods of Analysis in Food Safety Regulation, The Third Method, Apparatus B)								
<u>Standard Plate Counts</u>	Max. 1×10 ³ cfu/g (Analysis for Hygienic Chemists)								
<u>Moulds and Yeasts</u>	Max. 1×10 ² cfu/g (Analysis for Hygienic Chemists)								
<u>Coliforms</u>	Negative (Analysis for Hygienic Chemists)								
<u>Composition</u>	<table><thead><tr><th><u>Ingredient</u></th><th><u>Content</u> (Values are just a guide)</th></tr></thead><tbody><tr><td>Cyclodextrin</td><td>70 %</td></tr><tr><td>Rice extract</td><td>30 %</td></tr><tr><td>Total</td><td>100 %</td></tr></tbody></table>	<u>Ingredient</u>	<u>Content</u> (Values are just a guide)	Cyclodextrin	70 %	Rice extract	30 %	Total	100 %
<u>Ingredient</u>	<u>Content</u> (Values are just a guide)								
Cyclodextrin	70 %								
Rice extract	30 %								
Total	100 %								
<u>Expiry date</u>	3 years from date of manufacturing.								
<u>Storage</u>	Store it in a cool, dry, ventilated area with desiccant. Keep it away from high temperature and sunlight, and store it in a closed container.								

Established Date	August 19, 2015
Revised Date	January 29, 2024
Specification No.	U-429EN