

## ORYZA OIL & FAT CHEMICAL CO.,LTD.

1 Aza Numata Kitagata Kitagata-cho Ichinomiya-city, Aichi-prefecture 493-8001 JAPAN
Phone:+81-586-86-5141 Facsimile:+81-586-86-6191
URL/http://www.oryza.co.jp/ E-mail:info@oryza.co.jp

## PRODUCT STANDARD

## PRODUCT NAME: **JAPANESE BUTTERBUR EXTRACT-P** (FOOD)

This product is extracted with aqueous ethanol from Japanese butterbur, the stem and the leaves of *Petasites japonicus* (Compositae).

Appearance Certification Test

(1)Fukinolic acid

Slight yellowish powder with slight unique aroma.

After a small amount of methanol (HPLC grade) is added to 250mg of this product in a 10mL volume flask, and the flask is treated with ultra-sonic wave for 10 minutes. The solution is filtered through a 0.45  $\mu$  m PTFE filter after addition of methanol (HPLC grade) to adequate volume. For preparation of standard solution, methanol (HPLC grade) is added to fukinolic acid, and the concentration is prepared 0.1mg/mL (standard solution). HPLC analysis is performed according to the following conditions for 5  $\mu$  L of test solution and standard solution. The peak of fukinolic acid is found in the HPLC chromatogram of test solution.

< HPLC condition >

Column : capcellpak C18 (4.6 mm  $\phi \times 250$  mm) Mobile phase : Solvent A = Citric acid solution (citric acid monohydrate  $2.1g \rightarrow 1L$ )

Solvent B = Methanol

Condition of gradient

	8-11111							
Time(min)	0	19	25	35	50	60	61	70
Mobile	100%	100%	80%A	80%A	60% A	60%A	100%	100%
phase	Α	A	20%B	20%B	40%B	40%B	В	В

Flow rate : 1.0mL/min
Detector : UV 324 nm

Column temperature : 30°C

(2)Fukinone

This product (2.0g) in a centrifugation tube is suspended in purified water (10mL), and treated with ultra-sonic wave for 1 minute. Ethyl acetate (10mL) is added to the suspension, and the tube is shaken for 3 minutes. Then the tube is centrifuged (room temperature, 3000 rpm, 10minutes), and an ethyl acetate layer is collected (repeat this procedure three times) . The collected ethyl acetate layer is evaporated and is dissolved in 20% acetonitrile (3mL), and is filtered through a Sep-Pak C18 cartridge. Then, the cartridge is washed with 70% acetonitrile (7mL) and is eluted with absolute acetonitrile (5mL). This solution is adjusted to 10mL, and filtered through a 0.45  $\mu$  m PTFE filter (test solution). For preparation of standard solution, acetonitrile is added to fukinone, and the concentration is prepared 0.1mg/mL (standard solution). HPLC analysis is performed according to the following conditions for 5  $\mu$  L of test solution and standard solution. The peak of fukinone is found in the HPLC chromatogram of test solution.



## ORYZA OIL & FAT CHEMICAL CO.,LTD.

1 Aza Numata Kitagata Kitagata-cho Ichinomiya-city, Aichi-prefecture 493-8001 JAPAN

Phone:+81-586-86-5141 Facsimile:+81-586-86-6191 URL/http://www.oryza.co.jp/ E-mail:info@oryza.co.jp

< HPLC condition >

Column : Shim-pack CLC-ODS  $(6.0 \text{ mm } \phi \times 150 \text{ mm})$ 

Mobile phase : acetonitrile : water = 8:2

Flow rate : 1.0mL/min Detector : UV 254 nm

Column temperature :  $30^{\circ}$ C

**Total polyphenols** Min. 1.0 % (Folin-Denis method)

**Loss on Drying** Max. 10.0 % (Analysis for Hygienic Chemists,

1g, 105 °C, 2 hr)

**Purity Test** 

(1)Heavy Metals (as Pb) Max. 10 ppm (Sodium Sulfide Colorimetric Method) (2)Arsenic (as As<sub>2</sub>O<sub>3</sub>) Max. 1 ppm (Standard Methods of Analysis in Food

Safety Regulation, The Third Method,

Apparatus B)

Standard Plate CountsMax.  $3 \times 10^3$  cfu/g(Analysis for Hygienic Chemists)Moulds and YeastsMax.  $1 \times 10^3$  cfu/g(Analysis for Hygienic Chemists)ColiformsNegative(Analysis for Hygienic Chemists)

<u>Composition</u> <u>Ingredient</u> <u>Content</u> (Values are just a guide)

Maltodextrin 80 %

Japanese Butterbur Extract 20 %

Total 100 %

**Expiry date** 2 years from date of manufacturing.

**Storage** Store it in a cool, dry, ventilated area with desiccant.

Keep it away from high temperature and sunlight, and store it in a closed

container.

Established Date	June 5, 2004
Revised Date	May 28, 2020
Specification No.	T-028EN